




Development of a smart-and-connected irrigation system for rural communities in Nebraska

Jun Wang¹, Lorena Castro¹ Garcia¹, Zeyuan Ru¹, Nathan Janecek¹, Spencer Kuhl¹, Xin Qiao², Ximing Cai³, Alaa Jamal³, Haishun Yang², Daran Rudnick², Alian Kasabian² and Daniel Reed⁴





Yield/ha, Past & Future

Future. Extrapolated from past vs. required by population growth




Lack of soil and weather intelligence in real time

Damages by State from Billion-Dollar Disasters
(2018–2022)





In 2020, the KANI states had ~172 real-time weather stations, less than ~50% of 375 counties. Soil stations are far less.

This scarcity of weather and soil observation sites is in stark contrast with the large economic loss from weather and climate disasters and the large areas of socioeconomically disadvantaged communities,



Western Nebraska


~ 50 km x 30 km




I-Canopy System

- Temperature, RH, pressure at 2 m
- Soil moisture at 5 cm and 20 cm
- Soil temperature at 10 cm

For details, please see poster #: A15P-08.




Controller
WiFi



Air Sensor

LoRaWan
Antenna



Microcontroller: ESP32 (WiFi integrated)
Weather: BME280 (deployed) / BME680 (in testing)

Weather forecast & evaluation with sensor data in near real time


<https://esmc.uiowa.edu>

Home Weather Predictions Data Access Citizen Data LANCE Satellite Data Tutorials I-DARE About Us

UIOWA ESMC

Click on the circles to explore the sensors observations

Note: red suggests the need to change the battery, but COVID-19 pandemic made it difficult. We are in the processing to recover it.





Citizen environmental monitoring & forecast data

Time zone: America/Chicago



Plots Data

Refresh



Forecast Evaluation



Air temperature, RH, and Pressure




- Model overestimates T_{\min} , underestimates T_{\max} , has significant low bias in RH.
- Results suggest the impacts of the irrigation on the surface energy budget and weather parameters that are not considered in WRF prediction.

Forecast Evaluation


Soil temperature, 10 cm below surface



Irrigated




Rainfed




Irrigated

Irrigated fields clearly have lower soil temperature that are not captured by the model!

Irrigation Scheduling Optimization: Preliminary Results



- **Conventional: 178 mm**
- **Optimized: 106 mm**
- **Conventional Dry Matter: 13842 kg/ha**
- **Optimized Dry Matter: 15211 kg/ha**



Observation data helps to improve irrigation schedule optimization and lead to better outcomes!

Summary & Next Steps

- **Developed a I-Canopy sensor that can measure soil and air properties 24/7 in real time in the crop fields. We did it by considering:**
 - low cost solution for data transmission (LoRa)
 - Resiliency for weather changes (hot summer, cold winter, water proof; good and low-cost rechargeable batteries)
 - Power efficiency management (solar panel; reconnecting scheduling; avoid overcharging in summer and saving energy in winter)
 - Irrigated water from the side (impossible to measure air temperature during irrigation)
 - Calibrating soil moisture
- **The I-canopy data is now being integrated with the weather forecast model, crop model, and irrigation scheduling optimization. This smart-and-connected system was tested in 2022 and 2023 growing season.**
- **I-Canopy data can be used together with satellite data to provide improved mapping of weather and soil intelligence.**

Thank you !




United States Department of Agriculture
National Institute of Food and Agriculture


Award #: 2019-67021-29227

Details on sensor design: poster #: A15P-08

Hourly Soil Moisture 5cm




Hourly Soil Moisture 20cm






Hourly Soil Temperature (wrf at 5cm)



Hourly Soil Temperature (wrf at 20cm)




Cope with challenges in the irrigated crop field




- Air temperature needs to be measured in an open air environment.
- But, Stevenson Screen doesn't work in irrigated environment where water can penetrate the screen from the side and the below and damage the sensor.
- **Solution:** (a) put air sensor in the closed case to transmit the soil data only.
(b) Put canopy sensor in the nearby field that is not irrigated.

Hourly Soil Temperature (wrf at 5cm)




Hourly Soil Temperature (wrf at 20cm)



30-yr Normal Precipitation: Annual

Period: 1981-2010


Deficit of rainfall for crop growth



Annual Precipitation (in.)			
0	16 - 20	36 - 40	80 - 100
< 4	20 - 24	40 - 50	100 - 120
4 - 8	24 - 28	50 - 60	120 - 140
8 - 12	28 - 32	60 - 70	140 - 160
12 - 16	32 - 36	70 - 80	> 160



The smart-and-connected irrigation system

- Low-cost IoT-based sensors to measure soil moisture & temperature, air pressure, RH, and temperature
- Weather prediction model (WRF-Chem) run at 3 km resolution in real time
- Crop modeling for yield prediction and possible water deficit
- Optimization of irrigation schedule and delivery to stakeholders.



Key: community engagement; close collaboration between project team and local communities

Software and firmware




Soil temperature



Soil moisture




SM calibration curve




Soil moisture forecast at 3 km resolution

Temperature Intercomparison




0-10cm Soil Moisture ($m^3 m^{-3}$)



Crop Modeling

Estimated soil water status & crop water stress for the field "HY"



The real-time canopy measurements and weather forecast model outputs are now used to drive the crop model prediction of crop growth and when and how much water needs to be irrigated.